# **PTS Series**



## **PVC Transparent Stainless Steel Hose**



### **Features**

♦ The spiral high elastic steel wire is implanted into the hose wall, which makes the product has high axial strength. The inner and outer walls of the product are smooth and can withstand high pressure and vacuum compression. The product has good chemical resistance, acid resistance and alkali resistance



## **Applications**

 $\Diamond$  Usually used as suction and delivery hoses, such as solid powder, debris, particles, gas, liquid and so on

#### How to order

① Series	② Specification	3 length
PTS	D19, D25, D32, D45,	20, 40, 50m
	D50, D60, D75	

## **Technical parameters**

Model	Operating pressure range bar	Inner diameter mm	Outer diameter mm	Bending radius(Hose center line) mm	Weight kg/m	MPQ m
PTS-D19-50	0.2~7.0	19	25	100	0.32	50
PTS-D25-50	0.2~7.0	25	32	128	0.50	50
PTS-D32-40	0.2~7.0	32	41	164	0.65	40
PTS-D45-40	0.2~7.0	45	55	220	1.1	40
PTS-D50-40	0.2~7.0	50	60	256	1.24	40
PTS-D60-20	0.2~7.0	60	72	288	1.7	20
PTS-D75-20	0.2~7.0	75	89	356	2.15	20